


GL034

This product contains 1 light source(s) of energy efficiency E.



CODE	MATERIAL	AC	LED	T° (K)	LED Lumen	System Lumen
GL034DWBM27	STAINLESS STEEL 316	AC 230V	2,9W	2700K	240 Lm	170 Lm
GL034DWBM30	STAINLESS STEEL 316	AC 230V	2,9W	3000K	270 Lm	180 Lm
GL034DWBM40	STAINLESS STEEL 316	AC 230V	2,9W	4000K	280 Lm	190 Lm

ACCESSOIRES	DESCRIPTION	
JB5	IP68 PARALLEL CONNECTION BOX WITH GEL	
WC59	IP68 CONNECTOR	



Recessed wall mounting only.



Recessed floor mounting only.



Indoor and outdoor use.



Protected against the ingress of dust. Protected against jets of water.



Protection against an impact energy of 5 Joules.



Earth wire . Fixture equipped with primary insulation only.



Hole cut to insert luminaire. (80mm)



Hole cut to insert recessed housing. (85mm).



Beam 40°.



Product in conformity CE.



Colour rendering index >80.



LED specifications.



Power supply included.




Clean regularly with a suitable product to prevent corrosion. No mordant or abrasive material.




7 years warranty.





Replaceable control gear by an electrician.



Replaceable LED light source by an electrician.