


WL342

This product contains 1 light source(s) of energy efficiency F.





CODE	COLOR	MATERIAL	AC	LED	T° (K)	LED Lumen	System Lumen
WL341WW	CAST STAINLESS STEEL	STAINLESS STEEL 316	AC 230V	2,6W	3000K	205 Lm	50 Lm
WL342WW	BRUSHED BRASS	STAINLESS STEEL 316	AC 230V	2,6W	3000K	205 Lm	50 Lm
WL342AB27	ANTIQUE BRASS	ANTIQUE BRASS	AC 230V	2,6W	2700K	155 Lm	49 Lm
WL342AB30	ANTIQUE BRASS	ANTIQUE BRASS	AC 230V	2,6W	3000K	205 Lm	50 Lm





BRUSHED BRASS





ANTIQUE BRASS


ACCESSOIRES	DESCRIPTION	
JB5	IP68 PARALLEL CONNECTION BOX WITH GEL	
WC59	IP68 CONNECTOR	


 Recessed wall mounting only.


 Recessed floor mounting only.

 Indoor and outdoor use.


 Protected against the ingress of dust. Protected against jets of water.


 Earth wire . Fixture equipped with primary insulation only.


 Hole cut to insert luminaire. (80mm)


 Hole cut to insert recessed housing. (85mm).

 Beam 50°.

 Product in conformity CE.


 Colour rendering index >80.

 LED specifications.


 Power supply included.



7 7 years warranty.



Replaceable control gear by an electrician.



Replaceable LED light source by an electrician.