


CAIMAN VERSA

- Waterproof, corrosion-resistant linear luminaire.
- UV-resistant polycarbonate diffuser.
- 3000K, 4000K or 5700K selectable via a switch in the luminaire.
- Multi-power : 18 or 37W (AC4) and 28 or 56W (AC5) selectable via a switch in the luminaire.
- Non dimmable or dimmable DALI-push converter built in the device.
- Rear and side housing conduit entry points.
- Supplied with sliding mounting clips, hanging bracket and compression gland.
- Optional plug-in Versabox kits : emergency lighting, microwave sensor and remote control for setting the parameters of the detector.



This product contains light sources of energy efficiency class A.

CODE	COLOR	MATERIAL	AC	LED	T° (K)	LED Lumen	System Lumen	L (mm)
NOT DIMMABLE								
AC4N	GREY	POLYCARBONATE	AC 230V	18W 37W	3000-4000-5700K	3225 Lm (4000K) 6450 Lm (4000K)	2775 Lm (4000K) 5550 Lm (4000K)	1200
AC5N	GREY	POLYCARBONATE	AC 230V	28W 56W	3000-4000-5700K	4850 Lm (4000K) 9700 Lm (4000K)	4200 Lm (4000K) 8400 Lm (4000K)	1500
DALI DIMMABLE								
AC4D	GREY	POLYCARBONATE	AC 230V	18W 37W	3000-4000-5700K	3225 Lm (4000K) 6450 Lm (4000K)	2775 Lm (4000K) 5550 Lm (4000K)	1200
AC5D	GREY	POLYCARBONATE	AC 230V	28W 56W	3000-4000-5700K	4850 Lm (4000K) 9700 Lm (4000K)	4200 Lm (4000K) 8400 Lm (4000K)	1500

ACCESSOIRES DESCRIPTION

ACKITSELFEM SELF-TEST EMERGENCY KIT VERSABOX





ACKITMWS MICROWAVE SENSOR KIT VERSABOX





ACREMOTEMWS REMOTE CONTROL FOR MICROWAVE SENSOR




 Wall and ceiling mounting only.


 Indoor and outdoor use.


 Protected against penetration of dust
Protected against water jets.

 Protection against an impact energy of 20 Joules.


 Earth wire . Fixture equipped with primary insulation only.

 Beam 120°.

 Product in conformity CE.


 Colour rendering index >80.

 3 CCT.
3000K
4000K
5700K


 LED specifications.
LED
L70
100.000h


RG0 Photobiological risk RG0

650° Test on 650°.

 Power supply included.

7 7 years warranty.

 Replaceable control gear by an electrician.

 Replaceable LED light source by an electrician.