


CLARA 1 RDX

- Adjustable round semi-recessed spotlight.
- Fastened with springs.
- Remote dimmable converter supplied.
- Compatible with start and end-of-phase dimmer.

This product contains 1 light source(s) of energy efficiency G.





















CODE	COLOR	MATERIAL	AC	DC	LED	T° (K)	LED Lumen	System Lumen
DO534WW05	MATT BLACK	ALUMINIUM	AC 230V	DC 250mA 9V	3W	3000K	670 Lm	260 Lm
DO534WW30	MATT WHITE	ALUMINIUM	AC 230V	DC 250mA 9V	3W	3000K	670 Lm	260 Lm



MATT BLACK

MATT WHITE

-  Recessed ceiling mounting only.
-  Indoor use only.
-  Protected against the ingress of solid bodies greater 12 mm. No protection against the ingress of liquids.
-  Protection against an impact energy of 0,70 Joule.
-  Live parts are equipped with additional isolation protection, such as reinforced or double insulation.
-  Hole cut to insert luminaire (65mm)
-  Minimum ceiling height to insert luminaire. (130mm)
-  Vertical orientation maximum to 90°.
-  Horizontal orientation maximum to 350°.
-  Beam 36°.
-  Product in conformity CE.
-  CRI>80
-  LED specifications.
-  UGR below 19.
-  Photobiological risk RG1
-  Test on 650°.
-  Product can not be covered after installation even with insulation.
-  Power supply included.



250
mA

Connect to a constant current Led power supply of 250mA DC.




The product is dimmable.

5


5 years warranty.



Photometric data available on our website: www.indigo-lighting.com



Replaceable control gear by an electrician.



Replaceable LED light source by an electrician.