


# CLIC RDX MINI

- Adjustable round semi-recessed spotlight.
- Fastened with springs.
- Remote dimmable converter supplied.
- Compatible with end-of-phase dinner.

This product contains 1 light source(s) of energy efficiency G.



CODE	COLOR	MATERIAL	AC	DC	LED	T° (K)	LED Lumen	System Lumen
DO365SW05	MATT BLACK	ALUMINIUM	AC 230V	DC 200mA 37V	8W	2700K	710 Lm	435 Lm
DO365SW30	MATT WHITE	ALUMINIUM	AC 230V	DC 200mA 37V	8W	2700K	710 Lm	435 Lm
DO365WW05	MATT BLACK	ALUMINIUM	AC 230V	DC 200mA 37V	8W	3000K	750 Lm	467 Lm
DO365WW30	MATT WHITE	ALUMINIUM	AC 230V	DC 200mA 37V	8W	3000K	750 Lm	467 Lm



MATT BLACK



MATT WHITE



Recessed ceiling mounting only.



Indoor use only.



Protected against the ingress of solid bodies greater 12 mm. No protection against the ingress of liquids.



Protection against an impact energy of 0,20 Joule.



Live parts are equipped with additional isolation protection, such as reinforced or double insulation.



Hole cut to insert luminaire (68mm)



Vertical orientation maximum to 90°.



Horizontal orientation maximum to 355°.



Beam 38°.



Product in conformity CE.



CRI >90



LED specifications.



UGR below 19.



Photobiological risk RG1



Test on 650°.





Product can not be covered after installation even with insulation.





Power supply included.





 Connect to a constant current Led power supply of 200mA DC.

 The product is dimmable.

 3 years warranty.

 Photometric data available on our website: [www.indigo-lighting.com](http://www.indigo-lighting.com)

 Replaceable control gear by an electrician.

 Replaceable LED light source by an electrician.