


FILI 1 RX-B

- Adjustable round semi-recessed spotlight.
- Fastened with louvers.
- Remote non dimmable converter supplied.
- As an option, dimmable converter DALI CD123 to be ordered separately.

This product contains 1 light source(s) of energy efficiency G.



CODE	COLOR	MATERIAL	AC	DC	LED	T° (K)	LED Lumen	System Lumen
DO246WW05	MATT BLACK	ALUMINIUM	AC 230V	DC 250mA 37V	10W	3000K	1010 Lm	651 Lm
DO246WW30	MATT WHITE	ALUMINIUM	AC 230V	DC 250mA 37V	10W	3000K	1010 Lm	651 Lm



MATT BLACK



MATT WHITE

CODE	Watt Max	PRI	SEC	INPUTS	OUTPUTS	Max Case T°	Max Amb. T°
CD123	3-18W	AC 230V	DC 250mA	1	1	80°C	50°C



Recessed ceiling mounting only.



Indoor use only.



Protected against the ingress of solid bodies greater 12 mm. No protection against the ingress of liquids.



Protection against an impact energy of 0,20 Joule.



Live parts are equipped with additional isolation protection, such as reinforced or double insulation.



Hole cut to insert luminaire. (125mm)



Minimum ceiling height to insert luminaire. (100mm)



Vertical orientation maximum to 45°.



Horizontal orientation maximum to 355°.



Beam 40°.



Product in conformity CE.



CRI>90



LED specifications.



Photobiological risk RG1



Test on 650°.



Product can not be covered after installation even with insulation.





Power supply included.




Connect to a constant current Led power supply of 250mA DC.




3 years warranty.



Photometric data available on our website: www.indigo-lighting.com



Replaceable control gear by an electrician.



Replaceable LED light source by an electrician.