


JOY RX

- Adjustable round semi-recessed spotlight.
- Fastened with springs.
- Remote non-dimmable converter supplied.

This product contains 1 light source(s) of energy efficiency F.



CODE	COLOR	MATERIAL	AC	DC	LED	T° (K)	LED Lumen	System Lumen
DO510WW05	MATT BLACK	ALUMINIUM	AC 230V	DC 120mA 36V	4,5W	3000K	375 Lm	260 Lm
DO510WW30	MATT WHITE	ALUMINIUM	AC 230V	DC 120mA 36V	4,5W	3000K	375 Lm	260 Lm



MATT BLACK



MATT WHITE



Recessed ceiling mounting only.



Indoor use only.



Protected against the ingress of solid bodies greater 12 mm. No protection against the ingress of liquids.



Protection against an impact energy of 0,20 Joule.



Product can be connected to low-voltage systems. A safety extra low voltage luminaire in which voltages higher than those of SELV are not generated.



Hole cut to insert luminaire (35mm)



Minimum ceiling height to insert luminaire. (70mm)



Vertical orientation maximum to 90°.



Horizontal orientation maximum to 355°.



Beam 40°.



Product in conformity CE.



CRI>90



LED specifications.



UGR below 19.



Photobiological risk RG1



Test on 650°.



Product can not be covered after installation even with insulation.



Power supply included.



120
mA


Connect to a constant current Led power supply of 120mA DC.

3


3 years warranty.



Photometric data available on our website: www.indigo-lighting.com



Replaceable control gear by an electrician.



Replaceable LED light source by an electrician.