


## **OKTO RX GU10**

- Adjustable round semi-recessed spotloight.
- Fastened with springs.





CODE	COLOR	MATERIAL	SOCKET	AC	Watt Max	LAMP
DO51505	MATT BLACK	ALUMINIUM	GU10	AC 230V	13W	PAR16 LED
DO51508	MATT BLACK - CHAMPAGNE	ALUMINIUM	GU10	AC 230V	13W	PAR16 LED
DO51506	MATT BLACK - ROSE GOLD	ALUMINIUM	GU10	AC 230V	13W	PAR16 LED
DO51583	MATT BLACK - ROSE	ALUMINIUM	GU10	AC 230V	13W	PAR16 LED
DO51530	MATT WHITE	ALUMINIUM	GU10	AC 230V	13W	PAR16 LED
DO51549	MATT WHITE - CHAMPAGNE	ALUMINIUM	GU10	AC 230V	13W	PAR16 LED
DO51502	MATT WHITE - ROSE GOLD	ALUMINIUM	GU10	AC 230V	13W	PAR16 LED
DO51582	MATT WHITE - ROSE	ALUMINIUM	GU10	AC 230V	13W	PAR16 LED

















MATT BLACK

MATT BLACK -CHAMPAGNE

MATT BLACK - ROSE GOLD

K - ROSE MATT BLACK - ROSE

MATT WHITE

MATT WHITE -CHAMPAGNE

MATT WHITE - ROSE GOLD

MATT WHITE - ROSE



Recessed ceiling mounting only.



Indoor use only.



Protected against the ingress of solid bodies greater 12 mm. No protection against the ingress of liquids



Protection against an impact energy of 0,20 Joule.



Live parts are equipped with additional isolation protection, such as reinforced or double insulation.



Hole cut to insert luminaire (44 mm)



Minimum ceiling height to insert luminaire. (180mm)



Vertical orientation maximum to 85°.



Horizontal orientation maximum to 355°.



Product in conformity CE.



Test on 650°.



Product can not be covered after installation even with insulation.



3 years warranty.



Replaceable light source by an end-user.